

Installation/Inspection Code for Residential Gas Boilers

Personnel

Gas Technical Standards Committee

Chairman	Kwang-Won Lee, Professor of Hoseo University
Vice-Chairman	Seung-Hoon Nam, Principal Researcher of KRISS
Ex Officio Member	Hui-Won Lee, Manager of Energy Safety Department, Ministry of Trade, Industry & Energy
	Hae-Myeong Yang, Director of Technology and Safety, Korea Gas Safety Corporation
High-Pressure Gas	Seung-Hoon Nam, Principal Researcher of KRISS
	Beom-Seok Lee, Principal Professor of Kyung Hee University
	Dong-Myeong Ha, Professor of Semyung University
	Chang-Gi Kim, Principal Researcher of Korea Institute of Machinery and Materials
	Hyuk-Myun Kwon, Director General of Occupational Safety & Health Research Institute
	Su-Dong Byun, CEO of Q-Best
Liquefied Petroleum Gas	Doo-Seon Park, Managing Director of Daesung Industrial Gas Co., Ltd
	Hyeong-Hwan Ann, Professor of Korea National University of Transportation
	Byeong-Hak Choei, Professor of Gangneung-Wonju National University
	Seong-Min Lee, Director of KOGAS Research Institute
	Yong-Gwon Lee, Vice-President of EG CNE Co.,Ltd
	Gi-hyeon Jang, Director of Kiturmi
	Jeong-Sik Chon, Direto of E1 CO., Ltd.

KGS Code Establishment/Revision History				
Item Code No. KGS GC208 2020				
Code Name Installation/Inspection Code for Residential Gas Boilers				

Establishment/ Revision Date	Content	
Aug. 24, 2016	Established (Notification of the Ministry of Trade, Industry and Energy, No. 2016-430)	
Sep. 29, 2017	Revised (Notification of the Ministry of Trade, Industry and Energy, No. 2017-475)	
Aug. 10, 2018	Revised (Notification of the Ministry of Trade, Industry and Energy, No. 2018-419)	
Apr. 5, 2019	Revised (Notification of the Ministry of Trade, Industry and Energy, No. 2019-218)	
Mar. 18, 2020	Revised (Notification of the Ministry of Trade, Industry and Energy, No. 2020-167)	
	- End of Page -	

Table of Contents

1.	Gene	eral Ma	tters	2
	1.1.	Scope	e of Application	2
	1.2.	Effect	tiveness of Standard	3
	1.3.	Terms	s and Definitions	3
	1.4.	Appli	cation of Standard (No Content)	5
	1.5.	Interi	m Measures	5
	1	l .5.1 .	Interim Measures related to Installation Standard for Boilers	in
	F	acilities	s using an Urban Gas	5
	1	1.5.2.	Interim Measures related to Installation Standard for Boilers	in
	F	acilities	s using an LP Gas	7
	1	1.5.3.	Interim Measures for Joining of Flue Pipes	9
	1	1.5.4.	Interim Measures for Gas Boiler Installation Label	9
2.	Facili	ity Star	ndard	9
	2.1.	Gene	ral Requirements	9
	2	2.1.1.	Materials	9
	2	2.1.2.	Structure	10
	2	2.1.3.	Installation Method	10
		2.1.4.	Other Standard	
	2.2.	Indivi	dual/Direct Vent/Forced Flue Type	15
	2	2.2.1.	Materials (No Content)	15
	2	2.2.2.	Structure (No Content)	15
	2	2.2.3.	Installation Method	15
	2	2.2.4.	Other Standard (No Content)	
	2.3.	Indivi	dual/Vented/Forced Exhaust Type	19
	2	2.3.1.	Material (No Content)	19
	2	2.3.2.	Structure	19
	2	2.3.3.	Installation Method	
	2	2.3.4.	Other Standard (No Content)	20
	2.4.	Comn	mon/Vented/Forced Exhaust Type	20
	2	2.4.1.	Materials (No Content)	20
	2	2.4.2.	Structure	21
	2	2.4.3.	Installation Method	22

3.	Techi	nical S	tandard	24
	3.1.	Safet	y Maintenance Standard (N/A)	24
	3.2.	Trans	fer and Filling Standard (N/A)	24
	3.3.	Exam	ination Standard	24
	3	3.3.1.	Examination of Boiler	24
4.	Inspe	ection	Standard	24
	4.1.	Inspe	ection Items	24
	4	l.1.1.	Intermediate Inspection or Safety Check (N/A)	24
	4	l.1.2.	Completion Inspection	25
	4	l.1.3.	Regular Inspection	25
	4	l.1.4.	Occasional Inspection (N/A)	26
	4.2.	Inspe	ection Method	26
	4	l.2.1.	Intermediate Inspection (Safety Check) (N/A)	26
	4	1.2.2.	Completion Inspection and Regular Inspection	26
	4	1.2.3.	Occasional Inspection (N/A)	27
Ар	pendix	A Te	st Method for Properties of Plastic Materials (Related to 2.	1.1.1.1)
				28
Ар	pendix	в Ма	ain Items (Ratings) of Performance Certification Requireme	nts for
Pla	stic M	aterial	S	30
Ар	pendix	C Ins	tallation Standard for Gas Boilers in Facilities using an Urb	an Gas
bef	ore N	ov. 28,	1993	32
Ар	pendix	D In	stallation Standard for Gas Boilers in Facilities using anUrb	an Gas
aft	er Nov	<i>ı</i> . 28, 1	993 and before Aug. 24, 2017	53
Ар	pendix	EM	ethod to calculate Cross-sectional Area of Combined Co	ommon
Exł	naust C	Outlet	Inner Pipe (Related to Appendix D)	92
Ар	pendix	c F Inst	allation Standard for Gas Boilers in Facilities using an LP Gas	before
No	v. 28,	1993		101
Ар	pendix	G Ins	tallation Standard for Gas Boilers in Facilities using an LP Ga	as after
No	v. 28,	1993 a	and before Aug. 24, 2017	121

Installation/Inspection Code for Residential Gas Boilers

1. General Matters

1.1. Scope of Application

This standard applies to the installation of a gas boiler used for residential purpose {means the case where a gas boiler is used in a house, etc. as an individual exhaust type or for individual heating and, in the case where a gas boiler is used for central heating in an apartment, etc. or two or more gas boilers are used being connected with a flue pipe in a house, KGS GC209 (Installation/Inspection Code for Commercial and Industrial Gas Boilers) shall be applied} among the water heaters (exclusive of open type water heaters) and hot water boilers (hereinafter referred to as "gas boilers") pursuant to Attached Table 7, Subparagraph 4, Item i of the 「Enforcement Regulations of the Safety Control and Business of Liquefied Petroleum Gas Act」. However, the cases of the gas boilers of which the gas consumption exceeds 232.6 kW (200,000 kal/h) and the gas boilers which satisfy all the following conditions from (1) to (3) are excluded:

- (1) Gas boilers controlled by a safety manager pursuant to the 「Safety Control and Business of Liquefied Petroleum Gas Act」 (hereinafter referred to as "LP Gas Act") and the 「Urban Gas Business Act」 (hereinafter referred to as "Urban Gas Act") or an operator of the equipment subject to inspection pursuant to 「Energy Use Rationalization Act」
- (2) Gas boilers installed in the same room with a combustor that uses any other fuel than LPG and urban gas or a combustor of which the gas consumption exceeds 232.6 kW (200,000 kal/h)
- (3) Gas boilers equipped with a backflow preventer to prevent exhaust gas from flowing backward during operation or in a stationary state

Table 1.1 Application Standard by Installation Location and Form of Boiler

Classification		Application Standard
Single houses	Individual exhaust type	KGS GC208
	Cascade type	KGS GC209
A	For individual heating	KGS GC208
Apartments	For central heating	KGS GC209
	Individual exhaust type (not more than 70 kW)	KGS GC208

Ch a a a i a a	Individual exhaust type (more than 70 kW)	KGS GC209
Shopping centers,	Cascade type	KGS GC209
factories, etc.	Forced flue type (common connecting flue pipe)	KGS GC209

X KGS GC208: Installation/Inspection Code for Residential Gas Boilers

1.2. Effectiveness of Standard

- **1.2.1** This standard has been approved by the Minister of Trade, Industry and Energy (Notification of the Ministry of Trade, Industry and Energy, No. 2020-167, Mar. 18, 2020) after undergoing the deliberation/resolution of the Gas Technical Standard Committee established pursuant to Article 33-2 of the 「High-pressure Gas Safety Control Act」 (Agenda no. 2019-8, Oct. 18, 2019) in accordance with Article 17-5, Paragraph 2 of the Urban Gas Act and Article 45, Paragraph 2 of the LP Gas Act, and has an effect as a detailed standard pursuant to Article 17-5, Paragraph 1 of the Urban Gas Act and Article 45, Paragraph 1 of the LP Gas Act.
- **1.2.2** If this standard is complied with, the residential gas boiler shall be regarded to conform to Attached Table 7 of the 「Enforcement Regulations of the Urban Gas Act」 and Attached Table 20, Subparagraphs 1, 2, and 3 of the 「Enforcement Regulations of the LP Gas Act」 pursuant to Article 17-5, Paragraph 4 of the Urban Gas Act and Article 45, Paragraph 4 of the LP Gas Act <Revised on Aug. 10, 2018>.

1.3. Terms and Definitions

The meanings of the terms used in this standard are as follows:

- **1.3.1** "Flue pipe" means a pipe used to transfer exhaust gas of gas boilers such as a vent, connecting flue pipe, or a chimney.
- **1.3.1.1** "Vent" is related to a case where a gas boiler is used as an individual exhaust type and means a flue pipe through which the exhaust gas coming out of a gas boiler is directly discharged to the outside air without going through the connecting flue pipe or the chimney.
- **1.3.1.2** "Connecting flue pipe" is a flue pipe that connects a gas boiler to the chimney and means a pipe that connects the outlet of a gas boiler to the inlet of a chimney.

X KGS GC209: Installation/Inspection Code for Commercial and Industrial Gas Boilers